SSE-MPS-BASE

The SSE-MPS-BASE is a Heavy-Duty Stainless Steel Template designed to provide a single installation foundation for the V.I.T./Strong Box® MPS series of Metered Enclosures with the Calsense Stainless Steel Enclosures. This arrangement allows the easy installation of both products on to a single concrete pad, eliminating the need for additional installation equipment for each unit.

Two required items purchased directly from Calsense are:

- S1 or S2, SSE series of Stainless Steel Enclosures
- SSE-PED, Stainless Steel Enclosure Pedestal ٠

Items purchased directly from V.I.T./Strong Box are:

- SSE-MPS-BASE for their MPS Series Metered Enclosures and for the • installation of the Calsense SSE Enclosure
- MPS Model of Metered Enclosure •

description

The V.I.T./Strong Box MPS metered enclosure provides power distribution for street lighting, park lighting, private development lighting, signage, irrigation, pumps, and cellular applications. The 100% stainless steel welded construction provides ultimate protection against corrosion and vandalism. The V.I.T./Strong Box MPS metered enclosure features:

- Double door design
- . Stainless steel hinge
- Weather and vandal resistant
- Three-point locking system
- 10-year limited warranty •
- 0-200 amp load center with up to 30 circuits •
- 120v, 240v, and 480v models available •
- UL® listed, NEMA TYPE 3R rated •
- E.U.S.E.R.C. 308 compliant commercial metered pedestal

technical specifications

dimensions

- construction • Height: 52" • Material: 100% Stainless Steel
- Width: 18"
- Depth: 20"





V.I.T./Strong Box MODEL NUMBERS

MPS-A16-10K* METERED ENCLOSURE

- 100 amp meter/100 amp load center
- 16 pos. with main 1 phase

MPS-B16-10K* METERED ENCLOSURE

- 100 amp meter/150 amp load center
- 16 pos. with main 1 phase

MPS-C32-10K* METERED ENCLOSURE

- 200 amp meter/200 amp load center
- 32 pos. with main 1 phase

MPS-D18-10K* METERED ENCLOSURE

- 100 amp meter/100 amp load center
- 18 pos. with main 3 phase

MPS-E24-10K* METERED ENCLOSURE

- 200 amp meter/200 amp load center
- 24 pos. with main 3 phase

* All meter pedestals available with AIC rating of 22k, 65k and higher. Photocel, time clocks, lightning contactors and circuit breakers available factory installed.

Strong Box ia a registered trademark of V.I.T. Products, Inc. UL is registered certification mark of UL LLC.